



2	Pin header	Copper	Sn Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
VDE 标准/VDE Standard:	/	/	/
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	II/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	/	320/20
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	/	4
间距/Pitch(mm)/线数范围/ Poles	5.08/N=02~24P		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

SURFACE:

MATERIAL: 宁波三安电子科技有限公司  
Sanan Electrical Technology Co., Ltd

NAME: ZESAW-5.08-XXP-1Y-100A(H)

MAT NO.:  
STATUS:  
APPD:  
CHKD:  
DRT:

DRAWING NO.:  
SCALE:  
SHEET

公差/General tolerances(mm)	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	
	~	~	~	~	~	~	~	~	~	~	~	~	~	
	10	18	30	50	80	120	180	250	315	400	500	500	±2.50	
	±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50

SIZE: A4  
mm  
inch

TYPE:  
SCALE:  
SHEET